

STANDARD & HEAVY DUTY VALVE AND SERVICE BOXES

General Specifications

Material Valve and service boxes are produced with either Gray Iron ASTM A48 CL30/CL35 or Ductile Iron ASTM A536 : with standard lengths of 19'' - 82''. Standards Valve boxes are produced to meet the applicable American Association of State Highway and Transportation : Officials (AASHTO) provisions.

Castings are coated with asphaltic bituminous coating with minimum 1.5 mil thickness.

Series 6000 5 ¼" Shaft

Screw Type

Series 6100 5 ¼" Shaft Slip Type

LID LETTER OPTIONS*

IRRIGATION

* Default Lid Letter is 'WATER

WATER


SEWER

REUSE

GAS FIRE







LID 8 3/8 - 75/8 7 3/8 6 3/8

тор

воттом

LID LETTER OPTIONS*

WATER

SEWER

IRRIGATION

* Default Lid Letter is 'WATER

5 1/4

REUSE

GAS FIRE






* Default Lid Letter is 'WATER'

Series 6200 5 ¼" Shaft

Screw 3 Piece



6 5/8 7 1/8

TOP

97/16 7 3/4


1/2

14 1/4 17 1/4

#6 BASE



#60 EXTENSION



ᡞᡛᠲ᠕



Please refer to our web page www.sipindustries.com for up to date product data and technical advisories

8876 Gulf Freeway - Suite 500 - Houston, TX 77017 | Phone: 713-923-6111 | Fax: 713-923-6114 | www.sipindustries.com | sales@sipindustries.com