

MJ EYE BOLTS

MJ Eye Bolts also known as pigtails are used on a mechanical joint to create an anchor point for rods or bolts to secure components under pressure and for the compression of the MJ joint.




General Specifications


Material	:	Low alloy steel per ANSI/AWWA C111/121.11
Threads	:	UNC 2A Rolled Threads per ASME B1.1, Eye bolts can be used in place of T-Head bolts

Used on sizes 4" through 36"

Max. Load of each Eye Bolt: 7,500 lbs, engineered calculations on load

will determine the number of Eye Bolts needed.





Technical Specifications

Size	А	В	ØC
5∕8 x 3 ½	3.50	2.50	0.75
¾ x 3 ½	3.50	2.50	0.81
¾ x 4	4.00	3.00	0.81
¾ x 4 ½	4.50	3.00	0.81
¾ x 5	5.00	3.00	0.81
¾ x 5 ½	5.50	3.00	0.81
¾ x 8	8.00	3.00	0.81
1 x 6	6.00	5.00	1.06

Note: Some sort of washer needs to be used on the eye of the bolt to even the load from the Nut on the rod or bolt.

Please refer to our web page www.sipindustries.com for up to date product data and technical advisories

8876 Gulf Freeway - Suite 500 - Houston, TX 77017 | Phone: 713-923-6111 | Fax: 713-923-6114 | www.sipindustries.com | sales@sipindustries.com