

1" - 64" FLANGED FITTING ACCESSORY PACK

Submittal Information

Project Name / Location:	
Engineer:	
Referenced Specs:	
Distributor / Contractor:	

Optional Specifications

Bolts / Nuts:	O Carbon Steel: Type A307				
	Stainless Steel: Type 304 Type 316				
	Other - Specify:				
Gaskets:	Standard SBR (Buna-S) In Accordance With ANSI/AWWA C111/A21.11				
	Other - Specify:				

General Specifications

Material Bolt material is ASTM A307 Grade A, Zinc Plated (Stainless Steel available per request)

Nut material is ASTM A563 Grade A (Stainless Steel available per request)

Gasket material is as per ASTM D-2000 material.

Standard ANSI/ASME B 18.2.1, ANSI/ASME B 18.2.2

Hex Nuts are double chamfered per ANSI/ASME B18.2.2


Gaskets are 1/8" full face and manufactured in accordance with ANSI/AWWA C111/A21.11-00

Properties All bolts comply with the following properties:

> Brinell Hardness : 121 to 241 Tensile Strength :: 60 KSI min Elongation : 18% min

All Gaskets complies with the following properties:


: -10°F to 200°F Temperature Hardness : 75±5 (Shore A) Tensile Strength: 700 psi min : 150% Elongation Compression : 25% max Color : Red



Example of Star Pattern Tightening Sequence for 8 Bolt Flange

Technical Information

Select	Flange	Bolt			Bolt Torque
Size	Size	Qty.	Size	Weight	(Lb-Ft)
	*1	4	½ x 1 ¾	1	30
	*1 ½	4	½ x 2	1.1	30
	*2	4	5⁄8 x 2 1⁄4	1.6	50
	*2 ½	4	% x 2 ½	1.9	50
	3	4	% x 2 ½	2.5	50
	4	8	% x 3	3.3	90
	*5	8	¾ x 3	5.2	90
	6	8	34 x 3 ½	6	90
	8	8	34 x 3 ½	7	100
	10	12	% x 4	14	125
	12	12	% x 4	16	150
	14	12	1 x 4 ½	20	150
	16	16	1 x 4 ½	27	150
	18	16	1 1/8 x 5	38	200
	20	20	1 1/8 x 5	46	200
	24	20	1 ¼ x 5 ½	64	300
	30	28	1 ¼ x 6 ½	98	350
	36	32	1½x7	173	500
	42	36	1 ½ x 7 ½	216	500
	48	44	1 ½ x 8	265	535
	*54	44	1 ¾ x 8 ½	393	500
	*60	52	1 ¾ x 9	504	500
	*64	52	1 ¾ x 9	507	500



All dimensions are in inches unless noted otherwise.

All weights are approximate in pounds unless noted otherwise.

Supporting documentation for the above 'General Specifications' and 'Optional Specifications' are available upon request to review, in addition to Installation Instructions and any requested material samples

Please contact SIP for technical assistance of nonstandard applications

Please refer to our web page www.sipindustries.com for up to date product data and technical advisories

^{*} Flange Not Included In AWWA C110